



Price List May 2018



CONTENTS



S. No	Item	Page No.
1	MCCB and Adjustable MCCB	3
2	MCB , MEM DOL STARTERS, AUX BLOCK, WATER PUMP PRESSURE SWITCHES	4
3	Motor Protection Breakers, Enclosure, Auxiliary Blocks	5
4	Magnetic Contactors	6
5	Contactor Auxiliary Blocks, Coils, Suppressors	7
6	Miniature Contactors and Overload Relays	8
7	Overload Relays for Standard Contactors	9
8	Control Relays, Counters and Timers	10
9	Isolated Main Switches and Accessories	11
10	22mm Indication and Control Devices and Switches	12
11	Limit/Safety Switches (Including Non-Contact) and PLCs	13
12	Power Supplies	14



Moulded Case Circuit Breakers

3-POLE MCCB Fixed Current

S.No	Model	Current (A)	Breaking Capacity (kA)	Price (PKR)
1	BZMD1-A16	16A	15kA	PKR 9,000
2	BZMD1-A20	20A	15kA	PKR 9,000
3	BZMD1-A32	32A	15kA	PKR 9,000
4	BZMD1-A40	40A	15kA	PKR 9,000
5	BZMD1-A50	50A	15kA	PKR 9,000
6	BZMD1-A63	63A	15kA	PKR 9,000
7	BZMD1-A80	80A	15kA	PKR 9,000
8	BZMD1-A100	100A	15kA	PKR 9,000
9	BZMD1-A125	125A	15kA	PKR 17,600
10	BZMB2-A160	160A	25kA	PKR 20,300
11	BZMB2-A200	200A	25kA	PKR 25,700
12	BZMB2-A250	250A	25kA	PKR 25,700
13	BZMB3-A320	320A	25kA	PKR 42,800
14	BZMB3-A400	400A	25kA	PKR 42,800



4-POLE MCCB Fixed Current

S.No	Model	Current (A)	Breaking Capacity (kA)	Price (PKR)
15	BZMB1-4-A63	63A	25kA	PKR 27,000
16	BZMB1-4-A100	100A	25kA	PKR 27,000

3-Pole Adjustable MCCB

S.No	Model	Current (A)	Breaking Capacity (kA)	Price (PKR)
17	LZMB1-A125	100-125A	25kA	PKR 17600
18	NZMB2-A160	125-160A	25kA	PKR 57,800
19	NZMB2-A200	160-200A	25kA	PKR 69,500
20	NZMB2-A250	200-250A	25kA	PKR 77,000
21	NZMB2-A300	240-300A	25kA	PKR 96,300
22	NZMC3-A400	320-400A	36kA	PKR 112,300
23	LZMN3-AE630	315-630A	50kA	PKR 117,700
24	LZMN4-AE800	400-800A	50kA	PKR 214,000



Miniature Circuit Breakers (6kA)

Note: For 10kA, Price on Request



Pole	Model	Description	Ampere	RATE
Single	X-Pole	6kA, with Flag Indicator	1A & 3A	825/= Net
Single	X-Pole	6kA, with Flag Indicator	2A & 4A	720/= Net
Single	X-Pole	6kA, with Flag Indicator	6 to 32A	310/= Net
Single	X-Pole	6kA, with Flag Indicator	40A	385/= Net
Single	X-Pole	6kA, with Flag Indicator	50,63A	600/= Net
Single	X-Pole	6kA, with Flag Indicator	80,100A	2050/= Net

Double	X-Pole	6kA, with Flag Indicator	6 to 32A	1150/= Net
Double	X-Pole	6kA, with Flag Indicator	40,50,63A	1450/= Net

Triple	X-Pole	6kA, with Flag Indicator	6 to 32A	1600/= Net
Triple	X-Pole	6kA, with Flag Indicator	40,50,63A	2500/=Net
Triple	X-Pole	25kA, with Flag Indicator	100A	12650/= Net

Breaker Aux		
FAZ-XHIN11	1NO+1NC FAZ Breaker Aux	2350/=
ZP-IHK	1NO+1NC Aux for MmCM	2350/=



MEM DOL STARTER (3 Phase, 380-440V)

Model	HP	Current	Rate
ADS8	1	1.6-2.5A	6400/= net
ADS8	2	2.5-4A	6400/= net
ADS8	3	4-6A	6400/= net
ADS8	5	7-10A	6400/= net
ADS8	7	10-13A	6400/= net
ADS8	10	13-18A	6400/= net

WATER PUMP PRESSURE SWITCH

Model	Pressure Range (Psi)	Rate
CHWPS2040D	20 to 40 Psi	4000/=
CHWPS3050D	30 to 50 Psi	4000/=
CHWPS4060D	40 to 60 Psi	4000/=



Motor Protective Circuit Breakers

(GERMANY)



S.No	Model	Current (A)	Price (PKR)
25	PKZM0-0,16	0.1-0.16	PKR 9,000
26	PKZM0-0,25	0.16-0.25	PKR 9,000
27	PKZM0-0,4	0.25-0.4	PKR 9,000
28	PKZM0-0,63	0.4-0.63	PKR 9,000
29	PKZM0-1	0.63-1	PKR 8,000
30	PKZM0-1.6	1-1.6	PKR 8,000
31	PKZM0-2.5	1.6-2.5	PKR 8,000
32	PKZM0-4	2.5-4	PKR 8,000
33	PKZM0-6.3	4-6.3	PKR 8,000
34	PKZM0-10	6.3-10	PKR 8,800
35	PKZM0-16	10.0-16.0	PKR 8,800
36	PKZM0-20	16-20	PKR 10,000
37	PKZM0-25	20-25	PKR 10,800
38	PKZM0-32	25-32	PKR 13,200
39	PKZ-SOL-30		PKR 15400/= NET
40	PKZM4-40	32-40	PKR 24,500
41	PKZM4-63	55-63	PKR 29,400

Accessories



S.No	Model	Description	Price (PKR)
42	U-PKZO (220V, 50Hz)	UVT	On Request
43	U-PKZO (400V, 50Hz)	UVT	On Request
44	NHI11-PKZO	SIDE MOUNT AUX BLOCK 1NO+1NC	PKR 1,200/=
45	NHI11-E-PKZO	TOP MOUNT AUX BLOCK 1NO+1NC	PKR 1,200/=
46	NHI21-PKZO	SIDE MOUNT , 2NO + 1NC	PKR 2,500/=
47	CI-PKZO	Enclosure for PKZO	PKR 1,650/= net
48	CI-K2-PKZO	Enclosure for PKZ1	PKR 2,500/= net
49	CI-K2-PKZO-G	Enclosure for PKZ2	PKR 4,300/=



3-Pole Standard Magnetic Contactors (Romania)



S.No	Model	Auxiliary Contacts	AC1 (Ith) (A)	AC3 (Ie) (A)	kW	Price
50	DILM9-10 (AC)	1NO	20	9	4	PKR 2,700
51	DILM9-01 (AC)	1NC	20	9	4	PKR 2,700
52	DILM9-10 (24VDC)	1NO	20	9	4	On Request
53	DILM12-10 (AC)	1NO	20	12	5.5	PKR 3,300
54	DILM12-01(AC)	1NC	20	12	5.5	PKR 3,300
55	DILM12-10(24VDC)	1NO	20	12	5.5	On Request
56	DILM17-10(AC)	1NO	35	17	7.5	PKR 4,500
57	DILM17-01(AC)	1NC	35	17	7.5	PKR 4,500
58	DILM17-10(DC)	1NO	35	17	7.5	On Request
59	DILM25-10(AC)	1NO	40	25	11	PKR 6,000
60	DILM25-01(AC)	1NC	40	25	11	PKR 6,000
61	DILM25-10(DC)	1NO	40	25	11	On Request
62	DILM32-10(AC)	1NO	40	32	15	PKR 8,800
63	DILM32-01(AC)	1NC	40	32	15	PKR 8,800
64	DILM32-10(DC)	1NO	40	32	15	On Request
65	DILM40 (AC)		50	40	18.5	PKR 13,000
66	DILM40 (DC)		50	40	18.5	On Request
67	DILM50 (AC)		65	50	22	PKR 15,500
68	DILM50 (DC)		65	50	22	On Request
69	DILM65(AC)		80	65	30	PKR 19,800
70	DILM65(DC)		80	65	30	On Request
71	DILM80(AC)		90	80	37	PKR 27,000
72	DILM80(DC)		90	80	37	On Request
73	DILM95(AC)		110	95	45	PKR 32,000
74	DILM95(DC)		110	95	45	On Request
75	DILM115(AC)		130	115	55	PKR 53,000
76	DILM170 (AC)		185	170	90	PKR 82,500
77	DILM185(AC)	2NO+2NC	275	185	90	PKR 99,500
78	DILM225(AC)	2NO+2NC	315	225	110	PKR 130,000
79	DILM250(AC)	2NO+2NC	350	250	132	PKR 160,000
80	DILM300(AC)	2NO+2NC	400	300	160	PKR 198,000
81	DILM400(AC)	2NO+2NC	500	400	200	PKR 230,000
82	DILM500(AC)	2NO+2NC	700	500	250	PKR 306,000

Contactor AUXILIARY BLOCKS and COILS Suppressors



S.No	Model	Description	Price (PKR)
83	DILA-XHI11	TOP MOUNT 1NO+1NC for upto DILM32	PKR 1,500
84	DILA-XHI22	TOP MOUNT 2NO+2NC for upto DILM32	PKR 2,500
85	DILA-XHI02	TOP MOUNT 2NC for upto DILM32	PKR 1,500
86	DILA-XHI20	TOP MOUNT 2NO for upto DILM32	PKR 1,500
87	DILA-XHI40	TOP MOUNT 4NO for upto DILM32	PKR 2,500
88	DILA-XHI04	TOP MOUNT 4NC for upto DILM32	PKR 2,500
89	DILM150-XHI11	TOP MOUNT 1NO+1NC for DILM40 To 150	PKR 1,500
90	DILM150-XHI22	TOP MOUNT 2NO+2NC for DILM40 To 150	PKR 1,500
91	DILM1000-XHI11-SI	SIDE MOUNT 1NO+1NC for DILM40 to 1000	PKR 1,500
92	DILA-XHIV22	EARLY MAKE LATE BREAK TOP MOUNT 2NO+2NC	PKR 2,500
93	DILM95-XSPR240	SUPPRESSOR FOR DILM40 to DILM95, 110 to 240VAC	PKR 1000/= NET

S.No	Model	Description	Price (PKR)
94	02DILEM	TOP MOUNT 2NC	PKR 1,500
95	11DILEM	TOP MOUNT 1NO+1NC	PKR 1,500
96	22DILEM	TOP MOUNT 2NO+2NC	PKR 2,500
97	20DILE	TOP MOUNT 2NO	PKR 1,500
98	04DILE	TOP MOUNT 4NC	PKR 2,500
99	40DILE	TOP MOUNT 4NO	PKR 1,500
100	11DILE	TOP MOUNT 1NO+NC (Early make Late break feature)	PKR 1,500
101	22DILE	TOP MOUNT 2NO+2NC (Early make late break feature)	PKR 2,500

Coil For DILM Contactors

S.No	Model	Description	Price (PKR)
102	DILM32-XSP (AC)	AC coil for DILM17, 25, 32	On Request
103	DILM32-XSP (RDC)	DC coil for DILM17, 25, 32	On Request
104	DILM65-XSP (AC)	AC coil for DILM40, 50, 65	On Request
105	DILM65-XSP (RDC)	DC coil for DILM40, 50, 65	On Request
106	DILM95-XSP (AC)	AC coil for DILM80, 95	On Request
107	DILM95-XSP (RDC)	DC coil for DILM80,95	On Request



Miniature Contactors (Germany/Romania)

S.No	Model	Auxiliary Contacts	ACI (Ith) (A)	AC3 (Ie) (A)	kW	Price
108	DILA-40	4NO	16	4	1.6	PKR 3,300
109	DILA-31	3NO+1NC	16	4	1.6	PKR 3,300
110	DILA-31 (24VDC)	3NO+1NC	16	4	1.6	PKR 4,000
111	DILA-22	2NO+2NC	16	4	1.6	PKR 3,300
112	DILEM-01	1NC	20	9	4	PKR 3,800
113	DILEM-10	1NO	20	9	4	PKR 3,800
114	DILEM-10-G (24VDC)	1NO	20	9	4	PKR 4,200
115	DILEM-01-G (24VDC)	1NC	20	9	4	PKR 4,200
116	DILER-22	2NO+2NC	10	3	1.2	PKR 4,800
117	DILER-22-G (24VDC)	2NO+2NC	10	3	1.2	PKR 5,500
118	DILER-31	3NO+1NC	10	3	1.2	PKR 4,800
119	DILER-40	4NO	10	3	1.2	PKR 4,800
120	DILEM-4G	4NO	20	9	4	PKR 5,500

ZE Series Overload Relays (Use with DILE)

S.No	Model	Current (A)	Price (PKR)
121	ZE-0.16	0.1-0.16	PKR 4,600
122	ZE-0.24	0.16-0.24	PKR 4,600
123	ZE-0.6	0.4-0.6	PKR 4,600
124	ZE-1.0	0.6-1.0	PKR 4,600
125	ZE-1.6	1-1.6	PKR 4,600
126	ZE-2.4	1.6-2.4	PKR 4,600
127	ZE-4	2.4-4	PKR 4,600
128	ZE-6	4-6.0	PKR 4,600
129	ZE-9	6-9.0	PKR 4,600

Thermal Overload Relays

(GERMANY)



ZB Series (Use with DILM)



S.No	Model	Current (A)	Price (PKR)
130	ZB12-0.16	0.1-0.16	PKR 4,400
131	ZB12-0.24	0.16-0.24	PKR 4,400
132	ZB12-0.6	0.4-0.6	PKR 4,400
133	ZB12-1.0	0.6-1.0	PKR 4,400
134	ZB12 - 1.6	1-1.6	PKR 4,400
135	ZB12 - 2.4	1.6-2.4	PKR 4,400
136	ZB12-4	2.4-4	PKR 4,400
137	ZB12-6	4-6.0	PKR 4,400
138	ZB12 - 10	6-10.0	PKR 4,400
139	ZB32-16	10-16.0	PKR 4,400
140	ZB32 - 24	16-24	PKR 5,200
141	ZB32 - 32	24-32	PKR 5,700
142	ZB65 - 40	24-40	PKR 9,350
143	ZB65 - 57	40-57	PKR 9,350
144	ZB65 - 65	50-65	PKR 9,350

ZB150-35 (25-35A)	USE WITH DILM 80, 95, 115 & 150	13000/=
ZB150-50 (35-50A)	USE WITH DILM 80, 95, 115 & 151	13000/=
ZB150-70 (50-70A)	USE WITH DILM 80, 95, 115 & 152	13000/=
ZB150-100 (70-100A)	USE WITH DILM 80, 95, 115 & 153	13000/=
ZB150-125 (95-125A)	USE WITH DILM 80, 95, 115 & 154	18000/=
ZB150-150 (120-150A)	USE WITH DILM 80, 95, 115 & 155	18000/=
ZB150-175 (145-175A)	USE WITH DILM 80, 95, 115 & 156	18000/=

Control Relays, Timers and Counter



S.No	Old Model	New Model	Description	Price (PKR) NET
145		E5-024-C0400	Counter, Totalizing, E5 Series, 8 Digits, 24 x 48 mm, LCD, 4 Vdc to 30 Vdc, 12kHz, Battery Life: 8 YEARS,	9000/= NET
146		EMR5-W500-1-D	Phase failure, under/over voltage, Phase Sequence, On-Off delay adjustable 0.1 to 30 secs	11,000/= Net
147	ESR4-NO-21	ESR5-NO-21-24VAC-DC	Safety Relay, 2 Inputs, 24VAC/DC	26500/= NET
148		ESR5-NO-31-24VAC-DC	Safety Relay, 3 Inputs, 24VAC/DC	28600/= NET
149	ESR4-NE-42	ESR5-NE-51-24VAC-DC	Safety Relay, 5 Inputs, 24VAC/DC	On Request
150		ETR4-51-A	Star Delta Timer	9000/= Net
151		ETR4-69-A	Timer Multifunction, On and Off Delayed 2NC, 0.05 s-100 h, 24-240VAC/DC	9000/= net
152		ETR4-11-A	Timer Multifunction SPDT, ON DELAY, 0.05 s-100 h, 24-	9000/= net
153		ETR4-70-A	Timer Multifunction, 2NO+2NC, DPDT, on and off Delayed 0.05 s-100 h,	9000/= net
154		EMT6 (230VAC)	Thermistor Relay, 230VAC, Hand Reset	On Request
155		EMT6	Thermistor Relay (24-240VAC/DC)	On Request
156		EMT6-KDB	Thermistor Relay, Short Circuit Protection, Auto and Manual Reset. (24-240VAC/DC)	On Request

ISOLATED MAIN SWITCHES AND ACCESSORIES



157	T0-1-8200/I1/SVB	20A, 1 pole switch, with Box	3800/= Net
158	P1-25/I2/SVB	25A Load Break Rotary Disconnect Switch w/Box,	4200/= Net
159	P1-32/I2/SVB	32A Load Break Rotary Disconnect Switch w/Box,	4700/= Net
160	P3-63/I4/SVB	63A Load Break Rotary Disconnect Switch w/Box,	15950/= Net
161	P3-100/I5/SVB	100A Load Break Rotary Disconnect Switch w/Box,	21500/= Net
162	P5-125/V/SVB	125A, Rear Mounting WITHOUT BOX	25850/= NET
163	P5-125/EA/SVB	125A, Flush Mounting WITHOUT BOX	25850/= Net
164	P1-25/EA/SVB	25A Load Break Switch Flush Mount without Box	3850/= NET
165	P5-160/V/SVB	160A Load Break Switch, Rear Mount, 3 Pole without Box	29700/= Net
166	P5-250/V/SVB	250A Load Break Switch, Rear Mount, 3 Pole without Box	34500/= Net
167	P5-250/EA/SVB	250A Load Break Switch, Flush Mount, 3 Pole without Box	34500/= Net
168	P1-32/EA/SVB	32A Load Break Switch Flush Mount without Box	4200/= NET
169	P3-63/EA/SVB	63A Load Break Switch Flush Mount without Box	9400/= NET
170	P1-32/V/SVB	32A Load Break Switch Rear Mount without Box	4200/= NET
171	T3-3-8342/V/SVB	32A, 6 Pole, Rear mounting without BOX	13200/= Net
172	P3-63/V/SVB/N	63A, 4 pole, Rear Mounting WITHOUT BOX	18150/= Net
173	P1-25/M4/SVB	25A Main Switch with Stainless Steel Rod (400mm)	On Request
174	P1-32/M4/HI11/SVB- SW	32A Main Switch with 1NO+1NC Aux and Stainless Steel Rod (400mm) BLACK KNOB	On Request
175	P3-63/M4/K2-PR	63A Main Switch with Stainless Steel Rod (400mm)	On Request
176	T5B-4-15682/I4/SVB	63A, 6 pole, Main Switch with Box	24000/= NET
177	HI11-P1/P3E /	Auxiliary Block for Load Break (1NO + 1NC)	1500/= NET
178	N-P1E	Neutral Conductor 4th Pole for P1-25/E, P1-32/E	1000/= NET
179	N-P1Z	Neutral Conductor 4th Pole for P1-25/Z, P1-32/Z	1000/=NET

Indication and Control Devices

(Germany)



S.No	Model	Description	Price (PKR)
180	M22-D-G, R, S, B, W, Y	Push Button complete	PKR 1300
181	M22-DR-G, R	Latch Green Push Button complete	PKR 1750
182	M22-DP-G,R	Mushroom Type Push Button, complete	PKR 2850
183	M22-DDL-GR	Double Push Button complete with LED	PKR 3,000
184	M22-WRK	Selector Switch ON-OFF complete	PKR 1,650
185	M22-WRK3	Selector Switch ON-OFF-ON complete	PKR 2,000
186	M22 -WK3	Selector Switch Spring Return ON-OFF -ON	PKR 2,000
187	M22-WK	Selector Switch Spring Return ON-OFF	PKR 1650
188	M22-WR	Selector Switch 1-0 KNOB TYPE	PKR 2,200
189	M22-WRLKG, R, W	Illuminated Selector Switch ON-OFF	PKR 3,300
190	M22-WRLK3-G, R, W	Illuminated Selector Switch ON-OFF-ON	PKR 3,500
191	M22-DL-G, R, V, W, B	Illuminated Push Button	PKR 2,700
192	M22-DRL-G, R, B, Y, W	Latch Illuminated Push Button	PKR 3200
193	M22-WRS	Key Selector Switch ON-OFF	PKR 3,750
194	M22-WRS3	Key Selector Switch ON-OFF-ON	PKR 4,000
195	M22-PV	Emergency Stop Push Pull	PKR 2,400
196	M22-PVT	Emergency Stop Rotolock	PKR 2,900
197	M22-PVLT	Illuminated Emergency Stop Rotolock	PKR 6,000
198	M22-WJ4	JOYSTICK 4-WAY	PKR 13200
199	M22-XGPV	Emergency Stop Guard	PKR 1350/= NET
200	M22-PVS	Emergency Stop Key Operated	PKR 3,750
201	M22-L-G, R, V, W, B	Indication Light Complete (220V and 24VDC)	PKR 1,750
202	M22-LED-G, R, V, W, B	LED Block only (110/220V and 24VAC/DC)	PKR 1,200
203	M22-K01	NC Auxiliary Block	PKR 700
204	M22-K10	NO Auxiliary Block	PKR 700
205	M22-KC01	NC Auxiliary Block rear mount	PKR 900
206	M22-KC10	NO Auxiliary Block rear mount	PKR 900
207	FAK-R/V/KC11/IY	RED KNEE/PALM SWITCH 1NO+1NC with Box	PKR 13200
208	M22-I1	One Hole Box	PKR 1,650
209	M22-I2	Two Holes Box	PKR 2,000
210	M22-I3	Three Holes Box	PKR 2,300
211	M22-I4	Four Hole Box	PKR 3,500



LIMIT/SAFETY SWITCHES

S.No	Model	Description	Price (PKR)
212	AT4/11-S/I/R316	Slow Action Limit Switch, Adjustable Roller	8500/= NET
213	LS-11S/L	Snap Action Limit Switch, Plunger, Plastic,	4000/=
214	LS-S02-24DFT-ZBZ/X	Safety Interlock Switch, DPDT-NC, Screw	24000/= NET
215	LS-11S/P /	Plunger Snap Action	4000/=
216	LS-S02-ZB	Safety Switch, 2NC, Mini Body	10,500/=
217	LS-S11-ZB	Safety Switch, 1NO+1NC, Mini Body	10,500/=
218	RS2-12-C3	Safety Non Contact Magnetic Switch, 1NO + 2NC, Mini housing, wire type.	18500/=
219	RS4-12-Q6	Safety Non Contact Magnetic Switch, 1NO + 2NC, Long housing, plug type.	20,500/=

PLC

S.No	Model	Description	Price (PKR)
220	EASY719-AC-RC	Programmable Relay, easy700 Series, 12 Inputs, 6 Relay Outputs, 100 to 240 Vac, Clock, Display	20,000/= NET
221	EASY719-DC-RC	Programmable Relay, easy700 Series, 12 Inputs, 6 Relay Outputs, 24VDC, Clock, Display	22,500/= NET
222	EASY819-DC-RC	Programmable Relay, easy700 Series, 12 Inputs (4 analog inputs), 6 Relay Outputs, 24VDC, Clock, Display, Timers, Counters,	28500/= net
223	EASY-SOFT-PRO	Software Professional Version for EASY PLC	10,000/= Net
224	EASY800-USB-CAB	EASY800-USB-CAB / PC-USB-programm.c EASY-USB-CAB / PC-USB-programming c	9500/= NET
225	EASY-USB-CAB	EASY-USB-CAB / PC-USB-programming c	9500/= NET

Power Supplies

High-Performance, High-Quality



S.No	Model	Description	Price (PKR)
226	PSG60E24RM	2.5 A, 85 – 264 Vac 120 – 375 Vdc, 24VDC,	7500/= NET
227	PSG120E24RM	5 A, 85 – 264 Vac 120 – 375 Vdc, 24VDC,	10500/= NET
228	PSG240E24RM	10 A, 85 – 264 Vac 120 – 375 Vdc, 24VDC,	17500/= NET
229	PSG480E24RM	20 A, 85 – 264 Vac 120 – 375 Vdc, 24VDC,	26500/= NET
230	PSG480F24RM	20A, Three-phase units ("F" suffix): 320 – 575 Vac/450 – 800 Vdc	27500/= NET

PSG SPECIFICATIONS

Description	Specification
Input Voltage Range	Single-phase units ("E" suffix): 85 – 264 Vac/ 120 – 375 Vdc Three-phase units ("F" suffix): 320 – 575 Vac/450 – 800 Vdc
Input Frequency	47 – 63 Hz (0 Hz at dc input)
Input Fusing	All units are protected with internal fuse
Nominal Output Voltage	24 Vdc $\pm 2\%$
Output Voltage Adjustment	22 – 28 Vdc
Efficiency	>84% all models
Power Boost (Outrush/Current Surge)	150% of nominal current
Power Boost Time/Cycle	1 second @ 10-second intervals
Residual Ripple	<50 mV
Parallel Operation	Allowed with external ORing diode protection
Galvanic Isolation	Input/output, input/ground, output/ground
Housing Material	Aluminum (Al5052)
Signals	Green LED of dc OK
Operating Temperature	-20°C to +75°C (>50°C derating), <95% non-condensing RH
Certifications & Standards	UL®/cUL® listed-UL508, cURus-UL60950-1, CSA®, CE, IEC, German Safety, RoHS, EN 60204, EN 50178, PELV (EN 60204), SELV (EN 60950), DIN 57100-410, EN 610003-2, EN 61000-6-2, EN 61000-4-2...EN 61000-406, EN 61000-4-11, EN 61000-6-3

Further features:

- Adjustable output voltage range lets you configure the ideal settings for your application
- 150 % Power Boost for up to 5 s
- Wide operating temperature range: -25 °C up to +80 °C
- Protection from overvoltage and overcurrent conditions
- Rugged aluminum and plastic housings
- Redundancy modules
- New Buffer modul (Capacitor)
- NEC® Class II rating
- New finger-proof IP20 terminals with plug-in technology for single-phase devices
- DC OK LED indication

